

# 64 CYLINDER MEGC OFFSHORE UNIT

**Code: PB9667G**



|                                             |                |
|---------------------------------------------|----------------|
| <b>Design Temperature (°C)</b>              | -20/+65        |
| <b>Total volume, water capacity (litre)</b> | 3200           |
| <b>Cylinder diameter (mm)</b>               | 229            |
| <b>Max. height of cylinder</b>              | 1490           |
| <b>Max. gross weight (kg)</b>               | 8010           |
| <b>Payload (kg)</b>                         | 1670           |
| <b>Tare (kg)</b>                            | 6340           |
| <b>Max. working pressure (bar)</b>          | 300            |
| <b>Ext. dimensions (mm)</b>                 | 2175x1899x2444 |

- DNV-ST-E271 2.7-1 Offshore containers, ISO 10855, IMO/MSC Circular 860, NORSOK R-002 Lifting Equipment, IMDG Code, ADR, RID
- Designed to accommodate (x64) Ø229, 50L cylinders
- Includes full documentation pack
- (x64) cylinders @ 300bar WP
- Includes 300 bar cupri nickel manifold
- Includes (x64) cylinder valves
- (x4) inlet/outlet valves to suit gas service
- Includes pack build
- Includes wire rope sling set & shackles to DNV
- Hot dip galvanised finish

**Air   Argon   Heliox   Helium   Oxygen   Nitrogen**